


Art.-Nr. 1450

Sechskantschrauben
mit Schaft



verzinkt-passiviert

DIN	931
ISO	4014
Festigkeitsklasse	8.8
Zugfestigkeit	min. 800 N/mm ²
0,2% - Dehngrenze	min. 640 N/mm ²




d	M 3	M 4	M 5	M 6	M 7	M 8
k	2	2,8	3,5	4	4,8	5,3
S	5,5	7	8	10	11	13
b L < 125	12	14	16	18	20	22
b L > 125					26	28
Länge						
20	Available					
25	Available	Available		Available		
30	Available	Available	Available	Available	Available	Available
35	Available	Available	Available	Available	Available	Available
40		Available	Available	Available	Available	Available
45		Available	Available	Available	Available	Available
50		Available	Available	Available	Available	Available
55			Available	Available	Available	Available
60			Available	Available	Available	Available
65			Available	Available	Available	Available
70			Available	Available	Available	Available
75				Available	Available	Available
80			Available	Available	Available	Available
85				Available	Available	Available
90			Available	Available	Available	Available
100				Available	Available	Available
110				Available	Available	Available
120				Available	Available	Available
130					Available	Available
140						Available
150						Available
160						Available
200						Available

Andere Abmessungen auf Anfrage.

Art.-Nr. 1450

Sechskantschrauben
mit Schaft



verzinkt-passiviert

DIN	931
ISO	4014
Festigkeitsklasse	8.8
Zugfestigkeit	min. 800 N/mm ²
0,2% - Dehngrenze	min. 640 N/mm ²




d	M 10	M 12	M 14	M 16	M 18
k	6,4	7,5	8,8	10	11,5
S	17/16*	19/18*	22/21*	24	27
b L < 125	26	30	34	38	42
b L > 125	32	36	40	44	48
b L > 200	45	49	53	57	61
Länge					
35					
40					
45					
50					
55					
60					
65					
70					
75					
80					
85					
90					
100					
110					
120					
130					
140					
150					
160					
180					
200					
220					
240					
260					
280					
300					

* Neue SW nach ISO 272 (M10, M12, M14, M22)

Art.-Nr. 1450

Sechskantschrauben
mit Schaft



verzinkt-passiviert

DIN	931
ISO	4014
Festigkeitsklasse	8.8
Zugfestigkeit	min. 800 N/mm ²
0,2% - Dehngrenze	min. 640 N/mm ²



d	M 20	M 22	M 24	M 27	M 30	M 33	M 36
k	12,5	14	15	17	18,7	21	22,5
S	30	32/34*	36	41	46	50	55
b L < 125	46	50	54	60	66	72	78
b L > 125	52	56	60	66	72	78	84
b L > 200	65	69	73	79	85	91	97
Länge							
60							
65							
70							
75							
80							
90							
100							
110							
120							
130							
140							
150							
160							
180							
200							
220							
240							
260							
280							
300							

* Neue SW nach ISO 272 (M10, M12, M14, M22)