


# Art.-Nr. 1610

Sechskantschrauben UNF  
ohne / mit Schaft



verzinkt-passiviert\*

DIN	~933 / ~931
	UNF
Festigkeitsklasse	9
Zugfestigkeit	
0,2% - Dehngrenze	



Industribedarf

d	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	3/4"	
d mm	6,35	7,94	9,53	11,11	12,7	14,29	15,88	19,05	
Gänge	28	24	24	20	20	18	18	16	
b L<6"	19	22	25	28	32	35	38	44	
k	4	5,2	6	7,1	7,9	9,1	9,9	11,9	
s"	7/16"	1/2"	9/16"	5/8"	3/4"	13/16"	15/16"	1,1/8"	
s mm	11,11	12,70	14,29	15,88	19,05	20,64	23,81	29,58	
Länge									
1/2"	■								
5/8"	■								
3/4"	■								
7/8"	■								
1"	■								
1,1/4"	■			■					
1,1/2"	■					■			
1,3/4"	■								
2"	■							■	
2,1/4"	■								
2,1/2"	■								
2,3/4"	■								
3"	■								
3,1/4"	■	■					■		
3,1/2"	■								
3,3/4"	■			■					
4"	■								
4,1/2"	■						■		
5"	■		■					■	
5,1/2"	■			■					
6"	■				■				

oberhalb der Stufenlinie — ohne Schaft