


Art.-Nr. 2400

Gewindestifte

mit Innensechskant und Kegelkuppe



schwarz


| | |
|-------------|------|
| DIN | 913 |
| ISO | 4026 |
| Härteklasse | 45 H |



| d | M 2 | M 2,5 | M 3 | M 4 | M 5 | M 6 |
|--------|-----|-------|-----|-----|-----|-----|
| s | 0,9 | 1,3 | 1,5 | 2 | 2,5 | 3 |
| t min. | 0,8 | 1,2 | 1,2 | 1,5 | 2 | 2 |
| Länge | | | | | | |
| 3 | | | | | | |
| 4 | | | | | | |
| 5 | | | | | | |
| 6 | | | | | | |
| 8 | | | | | | |
| 10 | | | | | | |
| 12 | | | | | | |
| 14 | | | | | | |
| 16 | | | | | | |
| 18 | | | | | | |
| 20 | | | | | | |
| 25 | | | | | | |
| 30 | | | | | | |
| 35 | | | | | | |
| 40 | | | | | | |
| 45 | | | | | | |
| 50 | | | | | | |
| 55 | | | | | | |
| 60 | | | | | | |

Art.-Nr. 2400

Gewindestifte
mit Innensechskant und Kegelkuppe



schwarz

| | |
|-------------|------|
| DIN | 913 |
| ISO | 4026 |
| Härteklasse | 45 H |



Preise per 100 Stück

| d | M 8 | M 10 | M 12 | M 14 | M 16 | M 20 | M 24 |
|--------|-----|------|------|------|------|------|------|
| s | 4 | 5 | 6 | 6 | 8 | 10 | 12 |
| t min. | 3 | 4 | 4,8 | 5,6 | 6,4 | 8 | 10 |
| Länge | | | | | | | |
| 5 | | | | | | | |
| 6 | | | | | | | |
| 8 | | | | | | | |
| 10 | | | | | | | |
| 12 | | | | | | | |
| 14 | | | | | | | |
| 16 | | | | | | | |
| 20 | | | | | | | |
| 25 | | | | | | | |
| 30 | | | | | | | |
| 35 | | | | | | | |
| 40 | | | | | | | |
| 45 | | | | | | | |
| 50 | | | | | | | |
| 55 | | | | | | | |
| 60 | | | | | | | |
| 70 | | | | | | | |
| 80 | | | | | | | |
| 90 | | | | | | | |
| 100 | | | | | | | |