


Art.-Nr. 2330

Senkschrauben 90°
mit Innensechskant



verzinkt-passiviert

DIN	7991
ISO	~10642
Festigkeitsklasse	10.9
Zugfestigkeit	min. 1000 N/mm ²
0,2% - Dehngrenze	min. 940 N/mm ²



	M 3	M 4	M 5	M 6	M 8	M 10	M 12	M 16	M 20
d	3	4	5	6	8	10	12	16	20
b	12	14	16	18	22	26	30	38	46
dk	6	8	10	12	16	20	24	30	36
k	1,7	2,3	2,8	3,3	4,4	5,5	6,5	7,5	8,5
s	2	2,5	3	4	5	6	8	10	12
t max.	1,2	1,8	2,3	2,5	3,5	4,4	4,6	5,3	5,9
Länge									
6	Available								
8	Available	Available	Available	Available					
10	Available	Available	Available	Available					
12	Available	Available	Available	Available	Available				
14		Available	Available	Available	Available				
16	Available	Available	Available	Available	Available	Available			
18		Available	Available	Available	Available	Available			
20	Available	Available	Available	Available	Available	Available	Available		
22		Available	Available	Available	Available	Available			
25		Available	Available	Available	Available	Available	Available	Available	
30		Available	Available	Available	Available	Available	Available	Available	
35		Available	Available	Available	Available	Available	Available	Available	
40		Available	Available	Available	Available	Available	Available	Available	Available
45			Available	Available	Available	Available	Available	Available	
50			Available	Available	Available	Available	Available	Available	Available
55				Available	Available	Available	Available	Available	
60			Available	Available	Available	Available	Available	Available	Available
70				Available	Available	Available	Available	Available	Available
80				Available	Available	Available	Available	Available	Available
90					Available	Available	Available	Available	Available
100					Available	Available	Available	Available	Available