


Art.-Nr. 1660

Sechskantschrauben UNC
ohne / mit Schaft



verzinkt-passiviert*

DIN	~933 / ~931	
	UNC	
Festigkeitsklasse	8	.9
Zugfestigkeit		
0,2% - Dehngrenze		



Industribedarf

d	1/4"	5/16"	3/8"	7/16"	1/2"	9/16"	5/8"	3/4"
d mm	6,35	7,94	9,53	11,11	12,7	14,29	15,88	19,05
Gänge	20	18	16	14	13	12	11	10
b L<6"	19	22	25	28	32	35	38	44
k	4	5,2	6	7,1	7,9	9,1	9,9	11,9
s"	7/16"	1/2"	9/16"	5/8"	3/4"	13/16"	15/16"	1,1/8"
s mm	11,11	12,70	14,29	15,88	19,05	20,64	23,81	29,58
Länge								
3/8"								
1/2"								
5/8"								
3/4"								
7/8"								
1"								
1,1/4"								
1,1/2"								
1,3/4"								
2"								
2,1/4"								
2,1/2"								
2,3/4"								
3"								
3,1/4"								
3,1/2"								
3,3/4"								
4"								
4,1/2"								
5"								
5,1/2"								
6"								

oberhalb der Stufenlinie — ohne Schaft