


Art.-Nr. 1500

Sechskantschrauben

mit metrischem Feingewinde, mit Schaft



verzinkt-passiviert

DIN	960
ISO	8675
Festigkeitsklasse	8.8
Zugfestigkeit	min. 800 N/mm ²
0,2% - Dehngrenze	min. 640 N/mm ²



d	M8x1	M10x1,25	M12x1,25	M12x1,5	M14x1,5	M16x1,5	M18x1,5	M20x1,5
k	5,3	6,4	7,5	7,5	8,8	10	11,5	12,5
S	13	17/16*	19/18*	19/18*	22/21*	24	27	30
bL < 125	22	26	30	30	34	38	42	46
bL > 125					40	44	48	52
Länge								
35	Yes	Yes						
40	Yes	Yes	Yes	Yes				
45	Yes	Yes	Yes	Yes				
50	Yes	Yes	Yes	Yes	Yes	Yes		
55	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
60	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
65	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
70	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
80	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
90	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
100	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
110	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
120	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
130	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

Andere Abmessungen auf Anfrage.

* Neue SW gemäss ISO 272 (M10, M12, M14, M22)