


Art.-Nr. 6010

Splinten



DIN	94
ISO	1234



Federstahl, **verzinkt-passiviert**

Nenn-Ø	1	1,6	2	2,5	3,2	4	5	6,3	8	10	13
d1 max.	0,9	1,4	1,8	2,3	2,9	3,7	4,6	5,9	7,5	9,5	12,4
d1 min.	0,8	1,3	1,7	2,1	2,7	3,5	4,4	5,7	7,3	9,3	12,1
c max.	1,8	2,8	3,6	4,6	5,8	7,4	9,2	11,8	15	19	24,8
c min.	1,6	2,4	3,2	4	5,1	6,5	8	10,3	13,1	16,6	21,7
a max.	1,6	2,5	2,5	2,5	3,2	4	4	4	4	6,3	6,3
b~	3	3,2	4	5	6,4	8	10	12,6	16	20	26
Länge											
10	✓	✓	✓	✓	✓						
16	✓	✓	✓	✓	✓	✓					
20	✓	✓	✓	✓	✓	✓	✓				
25	✓	✓	✓	✓	✓	✓	✓	✓			
28	✓	✓	✓	✓	✓	✓	✓	✓	✓		
32		✓	✓	✓	✓	✓	✓	✓	✓	✓	
36			✓	✓	✓	✓	✓	✓	✓	✓	✓
40	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓
45			✓	✓	✓	✓	✓	✓	✓	✓	✓
50			✓	✓	✓	✓	✓	✓	✓	✓	✓
56				✓	✓	✓	✓	✓	✓	✓	✓
63					✓	✓	✓	✓	✓	✓	✓
71						✓	✓	✓	✓	✓	✓
80							✓	✓	✓	✓	✓
90								✓	✓	✓	✓
100									✓	✓	✓
125										✓	✓